

Model	UPC	Emissions Certification
3000psi @ 2.8 gpm		
6412	6 96471 06412 4	49-State
6414	6 96471 06414 8	50-State



features

VERSATILITY

- **PowerDial™** provides total control at the turn of a dial. Easily adjust the intensity of the spray to clean a wide range of different surfaces like automobile finishes, aluminum and vinyl siding, decks and fences and the toughest brick and concrete, all with a single, easy-to-use control.

EASE OF USE

- **Automatic System Protection** constantly monitors the oil and water level. If the oil or water runs low, the LED System Alert activates and automatically cuts power to the unit to protect it from damage.
- **Consolidated Control Panel** has all your controls in one easily accessible location.
- **Horizontal Axial Cam Pump** makes hose connections a snap.
- **Folding/Nesting Handle** provides compact storage.
- **Drainable Detergent Tank** allows for easily flushing chemicals from tank after each use.

POWER

- **Generac® 212cc OHV Engine** is the largest, most powerful engine in its class.
- Horizontally mounted engine and pump for improved system lubrication.

COMFORT

- **Comfort-Grip Handle** provides greater comfort for ease of use.
- **Ergonomic Inverted Trigger** reduces user fatigue.

MOBILITY

- **Wide, Never-Go-Flat 11" Wheels** provide easy transport regardless of terrain.
- **Precision Balanced** for stability and effortless mobility.

Residential Power Washers

specifications by model

Outlet Pressure - (PSI)/(BAR)	3000/207
Flow Rate - (GPM)/(Liters/min)	2.7/10.2
49 State	64120
CARB certified (50-State)	64140
Engine	
Engine Manufacturer	Generac
Engine Displacement (Cubic Inch)/(cc)	12.9/212
Engine Type	OHV (Over Head Valve)
Engine Orientation	Horizontal
Net Torque	12.5N.m (9.2 lb.ft)/3000rpm
Gross Power	7.0 Hp / 4000rpm
Low Oil Shut Down System	Yes
Fuel Capacity - (Quarts)/(Liters)	3.6/3.5
Oil Capacity - (Oz)/(Liters)	20/0.6
Recommended Engine Oil	SAE 30 or 10W30
Pressure Control	Manual
Choke	Manual
Starting Method	Manual
On/Off Switch	Yes
Pump	
Pump Type	Axial Cam
Plunger	Stainless Steel
Material	Aluminum Body, Brass Head
Misc	Double seal system with oversized bearings
Water supply temperature (°F)/(C°)	
Hose	
Hose length - (Feet)/(Meters)	30/9.1
Hose Dia. (Inch) / (mm)	1/4 / 6.4
Hose Rating	3100psi
Hose Connectors	M22 Threaded

Detergent System	
Chemical Tank - Description	3/4 Gallon
Nozzles	
Nozzles - Number per unit	3
Nozzles - Description	0, 25, Soap
Gun & Lance	
Gun	Standard
Gun to Lance Connection	M22 Threaded
Gun to Hose Connection	M22 Threaded
Lance Length (Inch/CM)	20/51
Lance to Nozzle Connection	Quick Change
Lance Material	Chrome Plated Steel
Lance Connector Material	Brass
Warranty	
Warranty	2 Yr. Limited
Frame & Misc.	
Handle	Folding
Construction	Welded Steel
Wheels	2.5" x 11" Never Flat
Dimensions and Weights	
Unit Dimensions (Inches) and Weight (lbs)	
Length (L)	22
Width (W) [Wheel to Wheel]	21
Height (H)	40
Unit weight including hose, gun & lance (lbs)	68.5
Actual boxed weight	75
Actual boxed length	22.25
Actual boxed width	22.0
Actual boxed height	22.0